LCD / LCM SPECIFICATION

RAYSTAR Optronics, Inc.
曜凌光電股份有限公司

曜凌光電股份有限公司
Raystar Optronics, Inc.
T: +886-4-2565-0761 | F: +886-4-2565-0760
salescontact@raystar-optronics.com | www.raystar-optronics.com

RC1602H

General Specification

The features is described as follow:

- Module Dimension: 59.0 x 29.3 x 5.5 (max.) mm
- View Area: 52.0 x 15.0 mm
- Active Area: 46.7 x 9.84 mm
- Number of Characters: 16 Characters x 2 Lines
- Dot Size: 0.45 x 0.54 mm
- Dot Pitch: 0.50 x 0.59 mm
- Character Size: 2.45 x 4.67 mm
- Character Pitch: 2.95 x 5.17 mm
- Duty: 1/16
- Backlight Type: Without Backlight
- IC: ST7066U
- Interface:68 series

RAYSTAR OPTRONICS

Interface Pin Function

Pin No.	Symbol	Level	Description
1	NC	—	No connection
2	V_{SS}	0V	Ground
3	V_{DD}	5.0V	Supply Voltage for logic
4	Vo	(Variable)	Operating voltage for LCD
5	RS	H/L	H: DATA, L: Instruction code
6	R/W	H/L	H: Read(MPU→Module) L: Write(MPU→Module)
7	E	H/L	Chip enable signal
8	DB0	H/L	Data bus line
9	DB1	H/L	Data bus line
10	DB2	H/L	Data bus line
11	DB3	H/L	Data bus line
12	DB4	H/L	Data bus line
13	DB5	H/L	Data bus line
14	DB6	H/L	Data bus line
15	DB7	H/L	Data bus line
16	NC	—	No connection

RAYSTAR OPTRONICS

Contour Drawing



PIN NO.	SYMBOL
1	NC
2	VSS
3	VDD
4	VO
5	RS
6	R/$\overline{W}$
7	E
8	DB0
9	DB1
10	DB2
11	DB3
12	DB4
13	DB5
14	DB6
15	DB7
16	NC



DOT SIZE
SCALE 10/1

The non-specified tolerance of dimension is ±0.3 mm .

RAYSTAR OPTRONICS

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	T_{OP}	-20	—	+70	℃
Storage Temperature	T_{ST}	-30	—	+80	℃
Input Voltage	V_I	V_{SS}	—	V_{DD}	V
Supply Voltage For Logic	V_{DD}-V_{SS}	-0.3	—	7	V
Supply Voltage For LCD	V_{DD}-V_o	-0.3	—	13	V

Electrical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For Logic	V_{DD}-V_{SS}	—	4.5	5.0	5.5	V
Supply Voltage For LCD	V_{DD}-V_0	Ta=-20℃	—	—	—	V
		Ta=25℃	3.6	3.7	3.8	V
		Ta=70℃	—	—	—	V
Input High Volt	V_{IH}	—	0.7 V_{DD}	—	V_{DD}	V
Input Low Volt	V_{IL}	—	Vss	—	0.6	V
Output High Volt	V_{OH}	—	3.9	—	V_{DD}	V
Output Low Volt	V_{OL}	—	0	—	0.4	V
Supply Current	I_{DD}	V_{DD}=5.0V	1.0	1.2	1.5	mA

RAYSTAR OPTRONICS